

Best Available Copy




(12) PATENT		(11) Application No. AU 200154153 B2	
(19) AUSTRALIAN PATENT OFFICE		(10) Patent No. 755374	
(54)	Title AV fistula and function enhancing method		
(51)⁷	International Patent Classification(s) A61F 002/06		
(21)	Application No: 200154153	(22)	Application Date: 2001.06.29
(30)	Priority Data		
(31)	Number 09/608734	(32) Date 2000.06.30	(33) Country US
(43)	Publication Date : 2002.01.03		
(43)	Publication Journal Date : 2002.01.03		
(44)	Accepted Journal Date : 2002.12.12		
(71)	Applicant(s) Vascular Architects, Inc.		
(72)	Inventor(s) Thomas J. Fogarty		
(74)	Agent/Attorney SPRUSON and FERGUSON,GPO Box 3898,SYDNEY NSW 2001		
(56)	Related Art US 6019788 WO 00/62711 WO 99/32051		

AV FISTULA AND FUNCTION ENHANCING METHOD

ABSTRACT OF THE DISCLOSURE

A coiled stent graft (10) is positionable within an AV fistula (4) and optionally into one or both of the artery (9) and the vein (6) to help reduce or eliminate blockages within
5 the blood vessel at the junction (8) between the AV fistula and the blood vessel.

PA 3068858 v1



AUSTRALIA

PATENTS ACT 1990

COMPLETE SPECIFICATION

FOR A STANDARD PATENT

ORIGINAL

Name and
Address
of Applicant : Vascular Architects, Inc.
1830 Bering Drive
San Jose California 95112
United States of America

Actual
Inventor(s): Thomas J. Fogarty

Address for
Service: Spruson & Ferguson
St Martins Tower, Level 35
31 Market Street
Sydney NSW 2000
(CCN 3710000177)

Invention Title: AV Fistula and Function Enhancing Method

The following statement is a full description of this invention, including the best method of performing it known to me/us:-

AV FISTULA AND FUNCTION ENHANCING METHOD

5

BACKGROUND OF THE INVENTION

10 A fistula is an abnormal passage typically between two organs, such as an artery and a vein. An arterio-venous (AV) fistula is a natural or an artificial graft, typically made of ePTFE (expanded PTFE), between a vein and an artery. An AV fistula, as used herein, also includes naturally-occurring native tissue tubular connections between a vein and an artery. AV fistulas are often used to provide multiple needle
15 access sites for hemodialysis. The AV fistula also helps to increase blood flow through the vein to accommodate the flow rate of blood needed for hemodialysis.

 One problem associated with AV fistulas is the progressive narrowing of the AV fistula at the junction with the vein. Such obstructions occur when vascular muscle cells begin growing inwardly causing, for example, thrombosis within the AV
20 fistula. When the thrombus becomes sufficiently large, blood flow decreases and the AV fistula ceases to be effective. It has been found that graft patency after six months is only 66% and that graft failure occurs, on the average, after 18 months.

 Improved graft patency has been achieved by the use of vascular clips instead of suturing the AV fistula to the vein. Variations in the angle of implantation
25 have also been shown to affect AV fistula patency. The use of a short length of a PTFE graft has been inserted in the vein to improve patency. (A.S. Coulson, et al., A Combination of the Elephant Trunk Anastomosis Technique and Vascular Clips for Dialysis Grafts, *Surgical Rounds*, 596-608, November 1999.) Also, a PTFE bypass graft to a proximal dilated vein has been used in response to the occurrence of graft-vein
30 stenosis. (Polo, J.R., The State of the Art of Surgical Treatment for Failing Grafts, The Seventh Biannual Symposium on Dialysis Access - Vascular Access for Hemodialysis VII, pp.8-9, May 2000.) Balloon angioplasty and endovascular stents may be used to treat stenosis in AV fistulas (J.E. Aruny, et al., Quality Improvement Guidelines for

Percutaneous Management of the Thrombosed on Dysfunctional Dialysis Access, JVIR, 10:491-498, April 1999.) However, there still exists the need to stop, or at least slow, the obstruction of the AV fistula to prolong the patency of the graft.

SUMMARY OF THE INVENTION

The present invention is directed to an AV fistula and a method for enhancing the function of an AV fistula by helping to prevent or at least retard the obstruction of the AV fistula at either or both the arterial and venous sides of the fistula.

A first aspect of the invention is directed to a method for enhancing the function of an AV fistula comprising:

selecting an endoluminal prosthesis comprising a generally helically-extending coiled body and a graft material at least partly covering the coiled body to create a coiled stent graft with generally helically-extending turns, said turns having an average width; and

placing the stent graft within an AV fistula and optionally within at least one blood vessel to which the AV fistula is connected.

The use of the stent graft helps to prevent, or at least retard, the obstruction of the AV fistula by eliminating, or at least reducing, the accumulation of matter in the AV fistula.

A second aspect of the invention is directed to a method for enhancing the function of an AV fistula comprising:

selecting an endoluminal prosthesis comprising a generally helically-extending coiled body and a graft material at least partly covering the coiled body to create a coiled stent graft with generally helically-extending turns;

placing the stent graft within the AV fistula and a vein so the stent graft extends across the junction between the AV fistula and the vein;

the selecting and placing steps being carried out so that the turns of the stent graft at the junction are separated by a gap so to not block fluid flow along the vein.

The turns of the stent graft at the junction may be spaced apart from one another so to insubstantially or partly hinder fluid flow along the vein. The turns of the stent may also be such as to effectively block fluid flow along the vein.

A third aspect of the invention is directed to an AV fistula assembly comprising:
an artificial AV fistula comprising a tubular body having a venous end and arterial end;

a coiled stent graft comprising a generally helically-extending coiled body and a graft material at least partially covering the coiled body;



the coiled stent graft having generally helically-extending turns, said turns having edges; and

the stent graft housable at least partially within the AV fistula at least one of venous and arterial ends.

5 A fourth aspect of the invention is directed to an AV fistula assembly comprising:

an artificial AV fistula comprising a tubular body having a venous end an arterial end;

10 a coiled stent graft comprising a generally helically-extending coiled body and a graft material at least partially covering the coiled body, the turns of the coiled stent graft being generally helically-extending and spaced-apart by gaps;

the lengths of the gaps varying by more than 100%; and

the stent graft housable partially within the AV fistula and extending past at least one of the venous and arterial ends.

15 Other features and advantages of the invention will appear from the following description in which the preferred embodiments have been set forth in detail in conjunction with the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

20 Fig. 1 is a side, partial cross-section view illustrating the venous end of an AV fistula with a stent graft extending from the AV fistula into the vein;

Fig. 2 illustrates the stent graft of Fig. 1 prior to placement into the AV fistula and vein;

25 Fig. 3 illustrates an alternative embodiment of the stent graft of Fig. 2 in which the pitch between two adjacent turns is substantially greater than the pitch between other of the turns to prevent restriction to fluid flow along the vein at the junction of the AV fistula;



Fig. 4 illustrates a further alternative embodiment of the stent graft of Fig. 2 in which the turns are adjacent to one another;

Fig. 5 illustrates the flattened end of the stent graft of Fig. 2 with the graft material removed to illustrate the stent; and

5 Fig. 6 illustrates an alternative embodiment of the stent of Fig. 5.

DESCRIPTION OF THE SPECIFIC EMBODIMENTS

Fig. 1 illustrates the venous end 2 of an AV fistula 4 joined to a vein 6 at a junction 8. The opposite end of AV fistula 4 is connected to an artery 9. The
10 construction of AV fistula 4 and the connections to artery 9 and vein 6 are conventional.

To help treat and/or prevent the obstruction or blockage 6 at junction 8, an endoluminal prosthesis in the form of a coiled stent graft, such as stent graft 10, is placed so that it extends within the venous end 2 of AV fistula 4 and within vein 6 so that stent graft 10 spans both sides of junction 8. Stent graft 10 is typically of a type in which the
15 turns 12 are generally evenly spaced apart from one another by gaps 14. While turns 12 of stent graft 10 may be evenly spaced when in a freely-expanded condition, as in Fig. 2, when placed within fistula 4 and vein 6, the gaps may not be the same from turn to turn. For example, Fig. 1 illustrates the situation in which gap 14A at junction 8 is somewhat larger than the other gaps 14. In some situations it may be desirable to use a stent graft
20 10A, shown in Fig. 4, in which the turns are adjacent to one another so that even at junction 8, turns 12 would be adjacent or closely spaced to effectively block fluid flow along vein 6 on one side of junction 8, that is the upstream (left) side in Fig. 1.

A typical AV fistula 4 has an inside diameter of about 4-10 mm and a length of about 2-10 cm. Stent graft 10 would typically have a slightly larger freely-
25 expanded outside diameter such as 5 mm for a 4 mm diameter AV fistula. The length of stent graft 10 typically depends upon the length of the AV fistula and whether the stent graft is to extend into one or both of vein 6 and artery 9. Thus, the length of stent graft 10 may range from, for example, 1 cm to over 10 cm.

Instead of the evenly spaced turns 12 of stent graft 10 of Figs. 1 and 2, a
30 stent graft 10B, see Fig. 3, could be used in which an extended gap 14B is provided between to adjacent turns 12B. Stent graft 10B may find particular use with gap 14B positioned at junction 8 to help ensure minimal restriction to fluid flow along vein 6 as well as from AV fistula 4 into vein 6.

A stent graft, having three sections with closely-spaced turns at the end sections and one or more loosely-spaced turns at the intermediate section, may be used. This embodiment may be used, for example, with one end section within fistula 4, the intermediate section at junction 8 and the other end section within vein 6. In addition, while the stent graft is typically a unitary item, it may be desirable to make the stent graft from two or more stent graft segments. For example, the stent graft could include three relatively short stent graft segments, one for placement in AV fistula 4, one for placement at junction 8 and one for placement along vein 6.

In the preferred embodiments stent grafts 10, 10A and 10B are made by covering wire stent blanks 16 (see Fig. 5) with a suitable graft material 15, such as ePTFE Dacron[®] polyester, polyurethane or natural vein. Stent blank 16 may be made of, for example, a temperature sensitive, shape memory alloy which tends to assume a radially extended position when at body temperature. Other means for expanding stent graft 10, such as or the application of an electric current or other energy source to heat the stent, or the use of simple spring stents, may also be used.

Fig. 5 illustrates one end of a stent blank 16, used to create stent grafts 10, 10A and 10B, prior to covering stent blank 16 with ePTFE graft material. Stent blank 16 comprises a pair of rails 18 connected by connectors 20, rails 18 being joined at their ends to form blunt ends 22. Blunt ends 22 are configured and constructed so to minimize trauma to patient tissue. Other types of stent structures may be used. For example, the angled connectors 20 of Fig. 5 could be replaced by one or more of perpendicular connecting elements, x-shaped connector elements, undulating connector elements or any of a variety of connector elements. Also, rails 18 could be discontinuous, which would occur, for example, when stent blank 16 is made of wire formed into a series of deep undulations, such as illustrated in Fig. 6. Other types of coiled stent structures made of a variety of biocompatible materials can be used as well. In the above-described preferred embodiments the entire stent blank is covered with graft material. In some situations it may not be necessary or desirable to cover the entire stent blank with graft material. Also, the stent blank may not have a constant width and the stent graft may have a diameter which changes over its length.

In use stent graft 10 may be placed into vein 6 when AV fistula 4 is initially grafted between the artery and vein. However, in the usual case stent graft 10 would not be used until the formation of some blockage at junction 8 has been observed. After any necessary removal of the blockage, stent graft 10 can be mounted to a suitable

placement catheter, such as one disclosed in U.S. Patent Application No. 09/400,952 filed September 22, 1999, and entitled "Catheter Assembly with Controlled Release Endoluminal Prosthesis". With stent graft 10 tightly wrapped about the placement catheter, the placement catheter is advanced percutaneously into vein 6, and then into
5 venous end 2 of AV fistula 4. Proper longitudinal and rotary placement of stent graft 10 can be monitored using remote visualization techniques, which may or may not involve the use of radiopaque markers carried by the stent graft. Radiopaque markers, when used, would likely be used at the ends of stent graft 10 and/or at the turn or turns 12 expected to be at or adjacent to junction 8 to help ensure proper placement. Once in position, stent
10 graft 10 is released from the placement catheter and is expanded to the position of Fig. 1.

To help eliminate any substantial hindrance to fluid flow along vein 6, stent graft 10 may be selected and placed so that the turns 12 at junction 8 are separated by a distance X. However, future testing may indicate that in some, or possibly all, cases it may be desirable to have turns 12 at junction 8 be positioned adjacent one another to
15 eliminate gap 14A and thus prevent fluid flow through the vein on the upstream (left) side of the junction.

Other modification and variation can be made to the disclosed embodiments without departing from the subject of the invention as defined in the following claims. For example, stent 10 could be a bifurcated, generally Y-shaped stent
20 graft.

Any and all patents, patent applications and printed publications referred to above are incorporated by reference.

The claims defining the invention are as follows:

1. A method for enhancing the function of an AV fistula comprising:

selecting an endoluminal prosthesis comprising a generally helically-extending coiled body and a graft material at least partly covering the coiled body to create a coiled stent graft with generally helically-extending turns, said turns having an average width; and

placing the stent graft within an AV fistula and optionally within at least one blood vessel to which the AV fistula is connected.

2. The method according to claim 1 wherein the placing step is carried out with the stent graft placed within the AV fistula and at least one blood vessel so the stent graft extends across the junction between the AV fistula and the at least one blood vessel.

3. The method according to claim 2 wherein the selecting and placing steps are carried out so that the turns of the stent graft at the junction are spaced-apart from one another so as to not block fluid flow through the blood vessel.

4. The method according to claim 2 wherein the selecting and placing steps are carried out so that the turns of the stent graft at the junction are next to one another so to effectively block fluid flow along the blood vessel on one side of the junction.

5. The method according to claim 1 wherein the placing step is carried out with the stent graft placed within the AV fistula and a vein.

6. A method for enhancing the function of an AV fistula comprising:

selecting an endoluminal prosthesis comprising a generally helically-extending coiled body and a graft material at least partly covering the coiled body to create a coiled stent graft with generally helically-extending turns;

placing the stent graft within the AV fistula and a vein so the stent graft extends across the junction between the AV fistula and the vein;

the selecting and placing steps being carried out so that the turns of the stent graft at the junction are separated by a gap so to not block fluid flow along the vein.

7. An AV fistula assembly comprising:

an artificial AV fistula comprising a tubular body having a venous end and arterial end;

a coiled stent graft comprising a generally helically-extending coiled body and a graft material at least partially covering the coiled body;

the coiled stent graft having generally helically-extending turns, said turns having edges; and



the stent graft housable at least partially within the AV fistula at least one of venous and arterial ends.

8. The assembly according to claim 7 wherein said edge of adjacent turns are adjacent to one another.

5 9. The assembly according to claim 7 wherein at least some of the turns are spaced-apart by gaps so that said spaced-apart turns do not overlap one another.

10. The assembly according to claim 9 wherein the gaps are generally equal in length.

10 11. The assembly according to claim 9 wherein the lengths of the gaps vary by more than 100%.

12. The assembly according to claim 7 wherein the coiled body comprises a framework of lateral rails and connectors.

13. The assembly according to claim 7 wherein the graft material is synthetic graft material.

15 14. The assembly according to claim 13 wherein the synthetic graft material is expanded PTFE.

15. An AV fistula assembly comprising:
an artificial AV fistula comprising a tubular body having a venous end an arterial end;

20 a coiled stent graft comprising a generally helically-extending coiled body and a graft material at least partially covering the coiled body, the turns of the coiled stent graft being generally helically-extending and spaced-apart by gaps;

the lengths of the gaps varying by more than 100%; and

25 the stent graft housable partially within the AV fistula and extending past at least one of the venous and arterial ends.

16. A method for enhancing the function of an AV fistula, said method substantially as described herein with reference to any one of the embodiments shown in the accompanying drawings.

30 17. An AV fistula assembly, said assembly substantially as described herein with reference to any one of the embodiments shown in the accompanying drawings.

Dated 21 August, 2002

Vascular Architects, Inc.

Patent Attorneys for the Applicant/Nominated Person

SPRUSON & FERGUSON



1/2




FIG. 1.



FIG. 2.




FIG. 3.



FIG. 4.




FIG. 5.




FIG. 6.

5
6
7
8
9

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

☒ **BLACK BORDERS**

☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**

☒ **FADED TEXT OR DRAWING**

☒ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**

☐ **SKEWED/SLANTED IMAGES**

☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**

☐ **GRAY SCALE DOCUMENTS**

☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**

☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**

☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.